

Evolis Tattoo Printer Specifications

Printing mode	Monochrome Thermal Transfer in Line Mode or Diffusion Mode for photo printing
Printer specification	Intagrated Ribbon Saver
Printing speed	500 cards/hour
Resolution	300 dpi (11.8 dots/mm)
Windows™ drivers	For Windows™ 95 / 98 / Me / NT 4.0 / 2000 and Xp
Warranty	Printer: 1 year Print Head: 1 year, unlimited number of prints ¹
Ribbons type	Mono Color Ribbon: 600 cards/roll Colors available: black, blue, red, green, white, gold, silver, scratch off
Card loading modes	Manual feeding and/or automatic feeding
Options	USB port (cable supplied) Serial port Additional interchangeable card feeder
Other printer models	Tattoo Mag Printer with HICO/LOCO magnetic stripe encoder - ISO 7811 Tattoo Stand - Alone Printer connected to a keyboard, available upon study

¹Clause governing the use of Evolis consumables

Other specifications

Card types: All PVC and Composite Polyester cards - **Card format:** ISO CR-80 - ISO 7810 (53.98mm x 85.60mm) - **Card thickness:** from 0,25mm (10mil) to 0.76mm (30mil) - **Card feeder capacity:** 100 cards (0,76mm-30mil) - 300 cards (0,25mm-10mil) - **Printer size:** Heigh: 166mm (6.53") - Width: 290mm (11.42") - Depth: 187mm (7.36") - **Printer weight:** 2,5kg (5.5lbs) - **Communication interface:** Centronics Parallel (cable supplied) - **Electrical:** 110~230 Volts CA, 60~50 Hertz - **Environmental :** Min / Max operating temperatures: 15°C / 30°C - Humidity: 20% to 65% non-condensing - Min / Max storage temperatures: -5°C / +70°C - Storage humidity: 20% to 70% non-condensing - Operating ventilation: free air.